

TF125



Way of Life!

The TF125 is characterized by its adaptability and its facility on all grounds. In addition to that this motorcycle is well know for its maintenance simplicity and its protections : perfect for intense usage on rough roads.



Colors available



MOTOR

Engine type	Single cylinder, 2-stroke
Displacement (cc)	123
Cooling system	Air-cooled
Compression ratio	6,2 : 1
Maximum power (Kw / rpm)	11Kw @ 6000 tr/min
Maximum power (hp / rpm)	15 / 7000
Maximum torque (N.m / rpm)	NC
Starter system	Kick starter
Lubrication system	Suzuki "CCI"
Ignition system	CDI
Fuel delivery	Suzuki "PEI"



CHASSIS

Frame	Steel cradle
Front suspension system	Telescopic fork, coil spring, oil damped
Rear suspension system	Swingarm type, coil spring, oil damped
Front brake	Drum
Rear brake	Drum
Wheels	Spoke
Front tyre	2,75-21 4PR
Rear tyre	4,10-18 4PR



DIMENSIONS

Overall dim - L x w x h (mm)	2170*935*1150
Wheelbase (mm)	1335
Seat height (mm)	835
Min ground clearance (mm)	250



TRANSMISSION

Transmission system	6-speed constant mesh
---------------------	-----------------------



WEIGHT/CAPACITIES

Dry weight (kg)	102
Fuel tank capacity (L)	13



EQUIPMENTS



Luggage rack



Kick starter



Spoke wheels

THE **2**
rules

1 Always wear a helmet, eye protection and protective proper clothing.

For more information, please contact your dealer Suzuki 2R.

2 Suzuki 2R encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

cfao
MOTORS