DT125



Its maintenance simplicity does the difference because no ground conditions can terrify the 2stroke engine and the monocross suspension of the DT125. Easy to repair, and cheap to maintain, this is one of the references of the governments, NGOs, and companies.



Colors availables











Engine type Single cylinder, 2-stroke 125 Displacement (cc) Cooling system Air-cooled 7,2:1 Compression ratio Maximum power (hp / rpm) 15 / 7000 Maximum torque (N.m / rpm) 15,2 / 6500 Starter system Kick starter Lubrification system Autolube Ignition system CDI Fuel delivery Carburetor



CHASSIS

Front suspension system Rear suspension system Front brake Rear brake

Double steel cradle Telescopic fork Swingarm (monocross) Drum Drum

6-speed

98

9.50

Wheels Spoke 2,75-21 4PR Front tyre Rear tyre 4,10-18 4PR



DIMENSIONS

Overall dim - L x w x h (mm) 2110*865*1165 Wheelbase (mm) 1340 830 Seat height (mm) Min ground clearance (mm) 260



TRANSMISSION







EQUIPMENTS





Transmission system

Fuel tank capacity (L)

Dry weight (kg)







Always wear a helmet, eye protection and protective proper clothing.

For more information, please contact your dealer YAMAHA.

YAMAHA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

cfao group

