

The EN125 is perfect for urban and extra urban rides, it assures reliability and resistance. It is well characterized as one of the best productivity for 125cc 4-stroke engine.





	MOTOR		
Ö		Engine type	Single cylinder, 4-stroke, SOHC
		Displacement (cc)	124
		Cooling system	Air-cooled
		Compression ratio	9,2 : 1
		Maximum power (hp / rpm)	12 / 9500
		Maximum torque (N.m / rpm)	NC
		Starter system	Electric starter
		Lubrification system	Wet sump
		Ignition system	CDI
	0110010	Fuel delivery	Carburetor
\square	CHASSIS	Frame	Steel cradle
		Front suspension system	Telescopic fork, coil spring, oil damped
		Rear suspension system	Swingarm link type, coil spring, oil damped
		Front brake	Simple disk
		Rear brake	Drum
		Wheels	Spoke
		Front tyre	2,75-18 42R MOTORS
		Rear tyre	90/90-18
r Å	DIMENSIONS		
		Overall dim - L x w x h (mm)	1945*735*1110
		Wheelbase (mm)	1265
		Seat height (mm)	750
		Min ground clearance (mm)	160
	TRANSMISSION		
0		Transmission system	5-speed constant mesh
Кд	WEIGHT/CAPACITIES		
		Dry weight (kg)	112
		Fuel tank capacity (L)	14
S.S.	EQUIPMENTS		
		Electric Disc Cast starter brake wheels	



Always wear a helmet, eye protection and protective proper clothing.

For more information, please contact your dealer Suzuki 2R.

Suzuki 2R encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

