



The "Africa" 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.

F9.9JMHL



TECHNICAL CHARACTERISTICS	F9.9JMHL
MOTOR	
Engine Type	In-line 4
Ignition System	Electronic Ignition (TCI)
Reduction ratio	56.0 X 43.0
Start-up	Electric with Prime Start™
Power system	1 carburetor
Lubrication system	Unleaded
Fuel consumption (L/h-tr/min)	3.9 L/h @5500 r/min
Fuel	Wet Sump
Full throttle operating range (tr/min)	5000-6000
Max.Prop Shaft Horsepower (Kw)	7.3 (9.9 hp)
Bore x Stroke (mm)	56.0 X 43.0
Architecture	L2
Displacement (cc)	212
MORE	
Propeller Rotation	Sens Horaire
Alternator	6 A
Control	Remote Control
DIMENSIONS	
Dry weight with propeller (kg)	45
Engine transom height (mm)	L : 558 (22.0 inch)
Oil capacity (L)	0.8 L
EQUIPMENTS	F9.9JMHL
Service kit assy.	✓
Fuel Tank comp.	✓
Fuel Pipe Comp.	✓
REGULAR PROPELLER (3 blades)	F9.9JMHL
Material	ALUMINUM
Diameter	8 1/2

Always wear a helmet, eye protection and protective proper clothing.
CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

